




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : C25B 9/00, 9/04, H01M 8/02, 8/24		A1	(11) International Publication Number: <b>WO 00/40780</b>
			(43) International Publication Date: 13 July 2000 (13.07.00)
(21) International Application Number: PCT/US99/30202 (22) International Filing Date: 17 December 1999 (17.12.99) (30) Priority Data: 60/114,557 31 December 1998 (31.12.98) US (71) Applicant: PROTON ENERGY SYSTEMS, INC. [US/US]; 50 Inwood Road, Rocky Hill, CT 06067 (US). (72) Inventors: BYRON, Robert, H., Jr.; 678 Beaumont Highway, Lebanon, CT 06249 (US). MOLTER, Trent, M.; 114 Harvest Lane, Glastonbury, CT 06033 (US). DRISTY, Mark, E.; Apartment 107, 141 John Olds Drive, Manchester, CT 06040 (US). (74) Agent: CURBELO, Pamela, J.; Cantor Colburn LLP, 55 Griffin Road South, Bloomfield, CT 06002 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: INTEGRATED MEMBRANE AND ELECTRODE SUPPORT SCREEN AND PROTECTOR RING FOR AN ELECTRO-CHEMICAL CELL



## (57) Abstract

The present invention is an integrated screen comprising a screen portion having openings and an integral protector edge disposed about the periphery of the screen portion. This integrated screen protector edge can be utilized individually as the membrane support/flow field in an electrochemical cell or in conjunction with one or more subsequent screen layers. When utilized with subsequent screen layers, the integrated screen protector edge is disposed adjacent to and in intimate contact with the membrane assembly.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## INTEGRATED MEMBRANE AND ELECTRODE SUPPORT SCREEN AND PROTECTOR RING FOR AN ELECTROCHEMICAL CELL

### BACKGROUND OF THE INVENTION

#### Field of the Invention

This invention relates generally to electrochemical cells, and especially relates to an integrated membrane, electrode support screen and protector ring that sustains the integrity and structure of the membrane.

#### Brief Description of the Related Art

Electrochemical cells are energy conversion devices, usually classified as either electrolysis cells or fuel cells, including, but not limited to, electrolysis cells having a hydrogen water feed. A proton exchange membrane electrolysis cell functions as a hydrogen generator by electrolytically decomposing water to produce hydrogen and oxygen gases. Referring to Figure 1, in a typical single anode feed water electrolysis cell 101, process water 102 is reacted at oxygen electrode (anode) 103 to form oxygen gas 104, electrons, and hydrogen ions (protons) 105. The reaction is created by the positive terminal of a power source 106 electrically connected to anode 103 and the negative terminal of a power source 106 connected to hydrogen electrode (cathode)

107. The oxygen gas 104 and a portion of the process water 102' exit cell 101, while protons 105 and water 102" migrate across proton exchange membrane 108 to cathode 107 where hydrogen gas 109, is formed.

5 The typical electrochemical cell includes a number of individual cells arranged in a stack with fluid, typically water, forced through the cells at high pressures (e.g., a pressure differential of about 30 psi from the cell inlet to the outlet). The cells within the stack are sequentially arranged including a cathode, a proton exchange membrane, and an anode. The cathode/membrane/anode assemblies (hereinafter "membrane and electrode assembly") are supported on either side by packs of screen or expanded metal,  
10 which are in turn surrounded by cell frames and separator plates to form reaction chambers and to seal fluids therein. The screen packs establish flow fields within the reaction chambers to facilitate fluid movement and membrane hydration, and to provide mechanical support for the membrane and a means of transporting electrons to and from the electrodes.

15 As stated above, the screen packs support the membrane and electrode assembly. The membrane is typically only about 0.002 - 0.012 inches in thickness when hydrated, and the electrodes are thin structures (less than about 0.002 inches) of high surface area noble metals pressed or bonded to either side of the membrane and electrically connected to a power source. When properly supported, the membrane  
20 serves as a rugged barrier between the hydrogen and oxygen gases. The screen packs, which are positioned on both sides of the membrane against the electrodes, impart structural integrity to the membrane and electrode assembly. Due to the high pressure differential that exists in an operating cell, however, the membrane and electrode on the low pressure side can be forced into the screen packs.

25 In the current state of the art, the membrane and electrode are clamped between the cell frames and supported in the active area by a screen pack or other similar porous device. (See Figure 2) By the nature and design of the assembly, there is a gap 122 between the frame component 124 and the screen pack 126 that the membrane and electrode assembly 128 must span. The pressure on one side of the membrane and  
30 electrode assembly 128 is generally higher than the pressure on the other side of the membrane and electrode assembly 128, and the membrane and electrode assembly,

must be capable of supporting this pressure differential. The gap 122 between the frame 124 and the screen pack 126 is generally too wide for the membrane and electrode assembly 128 to span and support the pressure differential without perforating. In addition, edges of the screen pack 130 often have burrs and/or other features that are likely to puncture the membrane and/or electrode.

Conventional screen packs have a number of disadvantages and drawbacks. For example, existing screen packs 26 comprise multiple layers of screen material formed from 0.005 inches (0.127 millimeters (mm)) - 0.010 inches (0.254 mm) thick metal strands having pattern openings of 0.125 inches (3.17 mm) by 0.053 inches (1.35 mm) to 0.071 inches (1.80 mm) (commonly known as 3/0 screen). Under typical operating conditions, a pressure differential of about 390 pounds per square inch (psi) forces the membrane assembly into the openings of the first layer of screen on the low pressure side of the cell. Due to the extrusion of the membrane into this screen layer, the membrane stress in the center of a screen opening increases to about 4,600 psi, while the membrane material has a maximum rating of only about 2,000 psi. Consequently, high axial stresses may force the screen strands into the membrane over time, thereby filling the screen void areas with membrane material. Alternatively, the membrane may rupture, allowing mixing of hydrogen and oxygen gases.

The current state of the art addresses both of the problems associated with pressure differentials and burrs by incorporating a thin metal or polymer protector ring 132 into the electrochemical cell. This ring 132 supports the pressure load imposed on the membrane and electrode assembly 128 over the gap 122 between the cell frame 124 and screen pack 126. The protector ring 132 also provides an impenetrable barrier for the membrane and electrode assembly 128 against the otherwise detrimental screen pack edge features 130.

However, protector rings used in conventional devices pose a number of problems for the construction and operation of the electrochemical cells. First, the protector ring is costly to manufacture, especially when made from materials suitable for use in an electrochemical cell, since much of the material is wasted in the fabrication process. Also, the protector ring is flimsy and difficult to position accurately in the cell assembly, and it is also prone to being dislodged from its intended

position during the handling associated with the cell assembly process. Finally, internal cell dynamics associated with repeated pressure cycles can cause relative motion between cell components, which may serve to mislocate the protector ring even after successful cell assembly. This may result in the membrane and electrode  
5 ultimately being exposed to the gap and screen pack edge, resulting in perforation and cell failure.

What is needed in the art is a readily manufactured, improved protector ring and screen assembly that provides protection for, and structural integrity to, the membrane and electrode, without adversely affecting the cell's mass flow characteristics.

10

#### Summary of the Invention

The above-described drawbacks and disadvantages of the prior art are alleviated by the integrated screen and protector ring, improved screen assembly, and electrochemical cell of the present invention. The integrated screen and protector ring  
15 comprises: at least one screen layer having openings and an integral protector edge about its periphery.

The improved screen assembly of the present invention comprises: a first screen layer having first openings and an integral protector edge about its periphery; and at least one subsequent screen layer having second openings, wherein said  
20 subsequent screen layer is disposed parallel to and in contact with said first screen layer.

The electrochemical cell of the present invention comprises: a membrane; an electrode disposed on each side of the membrane; and a screen assembly disposed adjacent to each of the electrodes, with at least one of the screen assemblies having a  
25 first screen layer having first openings and an integral protector edge about its periphery.

The above discussed and other features and advantages of the present invention will be appreciated and understood by those skilled in the art from the following detailed description and drawings.

30

### Brief Description of the Drawings

Referring now to the drawings wherein like elements are numbered alike in the several Figures:

Figure 1 is a schematic diagram of a prior art electrochemical cell showing an electrochemical reaction;

Figure 2 is a cross sectional view of a conventional electrochemical cell showing the relationship between the active site and the cell frame;

Figure 3 is a cross sectional view of an electrochemical cell showing the relationship of the cell components;

Figure 4 is a partial view of the integrated membrane and electrode screen support and protector ring of the present invention; and

Figure 5 is a cross sectional view of the electrochemical cell of the present invention showing the incorporation of the integrated membrane and electrode support screen and protector ring.

The Figures are meant to further illustrate the present invention and not to limit the scope thereof.

### Detailed Description of the Preferred Embodiment

The integrated screen and protector edge of the present invention comprises a combination of a screen and a protector ring for an electrochemical cell in a single component. Referring to Figure 3, the basic electrochemical cell 1 includes proton exchange membrane 8 having an anode electrode 3 and a cathode electrode 7 bonded to either side, with the periphery of membrane 8 installed between a pair of cell frames 21.

Oxygen screen pack 43 is installed inside the active area of the frame assembly between anode 3 and oxygen separator plate 45, while hydrogen screen pack 22 is installed inside of cell frame 21 between hydrogen separator plate 24 and cathode 7.

In the operation of one embodiment of an electrochemical cell of the present invention, process water 2 enters inlet port 25 and a portion of the water is diverted into oxygen screen pack 43. A portion of the water 2, not diverted into screen pack 43, continues along conduit 25 formed by axially aligned holes in the components comprising the stack and enters subsequent cells in the cell stack (not shown)

positioned outside of the cell 1. The portion of process water 2 diverted through screen pack 43 contacts anode 3 where the water electrochemically converts to oxygen gas and protons. Oxygen gas and excess water are exhausted from the cell through similar porting arrangements as those which directed the water to the anode 3. The generation  
5 of gases in the cell combined with external pressure regulation produces a large pressure differential between the oxygen side and the hydrogen side of the cell. This pressure differential forces membrane 8 and cathode 7 against the opposing screen pack. It should be noted that the direction of the pressure differential (greater or lower pressure on the cathode side) is dependent upon the application requirements of the  
10 electrochemical system.

Figure 4 shows an embodiment of the present invention with a partial view of the screen 112 with an integral protector edge 114 about its periphery. Although the integrated screen and protector edge 110 can be formed as one component or formed individually and bonded together, it is preferred to form this integrated component as  
15 one component, eliminating bonding requirements and possible problems, such as delamination, associated therewith. Possible production processes include those commonly known in the art, including, but not limited to, photochemical etching or laser cutting, which are preferred processes because they are inexpensive and they produce little waste.

20 The screen portion 112 of the integrated screen and protector edge 110 should be formed from an electrically conductive material. Possible materials for the integrated screen portion 112 include metals, polymers, and combinations thereof suitable for use with electrochemical cells, preferably in the form of a thin sheet. The thickness of the sheet, which is system dependent, is typically less than about 0.005  
25 inches, with about 0.002 inches to about 0.004 inches preferred, and about 0.0025 inches to about 0.0035 inches especially preferred. Suitable metals and polymers include steel, such as stainless steel, nickel, niobium, zirconium, cobalt, tantalum, titanium, elastomers, thermoplastic or thermosetting polymers, ceramics, polyetherimide, polysulfone, polyether sulfone, polyethylether ketone, and other  
30 metals, metal alloys, other materials, and polymers, and mixtures and combinations thereof.

Although the integrated screen and protector edge 110 can be employed as the membrane support/fluid flow field, it is typically utilized in a subassembly 134 comprising the integrated screen protector edge 110 bonded or otherwise disposed adjacent to and in intimate contact with at least one, and preferably a plurality, of subsequent screen layers 136 (see Figure 5). These screen layers 136 can similarly be formed from electrically conductive material, such as etched or perforated sheets or a woven metal mesh, and are typically composed of material including steel, such as stainless steel, nickel, niobium, zirconium, cobalt, tantalum, titanium, among others and alloys thereof. The geometry of the openings in the screen and subsequent screen layers can range from ovals, circles, and hexagons, to diamonds and other elongated shapes. An especially preferred screen assembly for use in electrochemical cells is disclosed in commonly assigned U.S. Patent Serial No. 09/102,305, to Trent M. Molter, Attorney Docket No. 97-1801 (herein incorporated by reference).

The integrated screen and protector edge 110 is preferably integrated into the overall subassembly 134, as shown in Figure 5, via a tack weld process, bonded to the supporting frame (i.e. to the integrated screen/protector edge) using an adhesive material, or other conventional process known in the art. The tack weld process creates a subassembly 134 that is easy to handle and is self locating within the cell.

The integrated screen and protector edge 110 or the subassembly 134 supports a membrane assembly composed of a cathode/membrane/anode arrangement, wherein the cathode and anode are disposed in intimate contact with the membrane, and an integrated screen-protector edge is disposed in intimate contact with the cathode and anode accordingly. The membrane can be any conventional membrane, including, but not limited to, proton exchange membranes including homogeneous perfluoroionomers such as Nafion® (commercially available from E.I. duPont de Nemours and Company, Wilmington, DE), ionomer Teflon® composites such as Gore Select® (commercially available from W.L. Gore Associates, Inc., Elkton, MD), styrene, divinyl benzene, and mixtures thereof. Similarly, the cathode and anode electrodes can be conventional electrodes composed of materials such as platinum, palladium, rhodium, carbon, gold, tantalum, tungsten, ruthenium, iridium, osmium, alloys thereof and other catalysts capable of electrolyzing water and producing hydrogen.

The advantages of incorporating the integrated screen and protector edge of the present invention into the screen pack subassembly are immediately apparent considering the fact that the protector edge 114 (See Figure 4), which is an integral part of the screen pack protector ring subassembly 134, is no longer subject to mislocation  
5 due to cell pressure cycles. Indeed, it is essentially mechanically locked into its position relative to the gap 122 of the electrochemical cell frame 124. Also, the protector ring is effectively stabilized due to its combination with the support screen, resulting in a stronger, more durable product with a lower fabrication cost relative to the production of separate parts.

10 Further, incorporation of the screen pack subassembly into the electrochemical cell, as shown in Figure 5, results advantageously in rigid protection of the membrane and electrode assembly 128 from both pressure differentials across the active site of the cell, and membrane ruptures that might otherwise be caused by burrs 130 along the edge of the screen pack. As such, the present invention represents a substantial  
15 increase in the durability and effective lifetime of electrochemical cells with a low cost of fabrication.

Although the present invention has been described in relation to an electrolysis cell, it is understood that the integrated screen and protector edge can be employed in all electrochemical cells, e.g. anode feed water and cathode feed water electrolysis  
20 cells, and fuel cells. It is further understood that the details of the electrochemical reactions, preferred reactants, and preferred components will change accordingly, as is conventionally understood.

While preferred embodiments have been shown and described, various modifications and substitutions may be made thereto without departing from the spirit  
25 and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

What is claimed is:

## CLAIMS

1. An integrated screen and protector edge, comprising:  
a screen portion having openings; and  
an integral protector edge disposed about the periphery of said screen portion.
2. The integrated screen and protector edge of Claim 1, wherein said screen portion and said protector edge are formed by the process of photochemically etching the protector ring to said screen portion.
3. The integrated screen and protector edge of Claim 1, wherein said screen portion and said protector edge are formed by the process of laser cutting said protector edge and said screen portion together.
4. A screen subassembly, comprising:  
a first screen layer having a screen portion having first openings;  
an integral protector edge disposed about the periphery of said screen portion;  
and  
at least one subsequent screen layer having second openings, wherein said subsequent screen layer is disposed parallel to and in contact with said first screen layer.
5. The screen subassembly of Claim 4, wherein said first screen layer is tack welded to said subsequent screen layer.


6. An electrochemical cell, comprising:  
a membrane;  
an electrode disposed on each side of said membrane to form a membrane  
assembly; and

5 at least one integral screen protector edge, said screen protector edge having a  
first screen portion having first openings with an integral protector edge disposed about  
the periphery of said first screen portion, said integral screen protector edge disposed in  
intimate contact with said membrane assembly.

7. An electrochemical cell as in Claim 6, further comprising at least one  
subsequent screen layer having second openings, wherein said subsequent screen layer  
is disposed parallel to and in contact with said first screen portion.

1/2

FIG. 1  
Prior Art



2/2

FIG. 2




FIG. 3




FIG. 4





FIG. 5



# INTERNATIONAL SEARCH REPORT

In ☐ national Application No

PCT/US 99/30202

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C25B9/00 C25B9/04 H01M8/02 H01M8/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C25B H01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 275 466 A (DOW CHEMICAL CO) 27 July 1988 (1988-07-27) column 3, line 35 - line 47 column 5, line 30 - line 49 column 6, line 26 - line 36 column 7, line 6 - line 9	1,6
A	WO 98 24136 A (UNITED TECHNOLOGIES CORP) 4 June 1998 (1998-06-04) page 4, line 16 - line 23 page 5, line 31 - page 6, line 19 page 8, line 10 - line 19 claim 1; figures 1,2	1,2,4,6, 7

-/-



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

29 May 2000

Date of mailing of the international search report

07/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Gamez, A

# INTERNATIONAL SEARCH REPORT

Int. Patent Application No  
PCT/US 99/30202

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	WO 99 61684 A (PROTON ENERGY SYSTEMS) 2 December 1999 (1999-12-02) page 3, line 16 - line 25 page 5, line 9 - line 13 page 7, line 6 - line 18 page 10, line 29 -page 11, line 13 claims 6,7,25; figures 3,13	1,4,6
P,A	WO 99 27599 A (FUGLEVAND WILLIAM A ;AVISTA LABS (US)) 3 June 1999 (1999-06-03) page 32, line 16 -page 33, line 10 figures 12,28	1,6

# INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/US 99/30202

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0275466 A	27-07-1988	US 4752370 A	21-06-1988
		US 4889577 A	26-12-1989
		AT 81162 T	15-10-1992
		AU 582059 B	09-03-1989
		AU 8219887 A	07-07-1988
		CN 1034763 A,B	16-08-1989
		DE 3782026 A	05-11-1992
		DE 3782026 T	18-02-1993
		FI 875561 A	20-06-1988
		JP 1512191 C	09-08-1989
		JP 63058917 B	17-11-1988
		JP 63179088 A	23-07-1988
		KR 9000572 B	31-01-1990
		NO 875321 A	20-06-1988
		ZA 8709467 A	30-08-1989
		BR 8705141 A	11-04-1989
		CN 1034764 A,B	16-08-1989
WO 9824136 A	04-06-1998	EP 0947020 A	06-10-1999
WO 9961684 A	02-12-1999	AU 4089499 A	13-12-1999
WO 9927599 A	03-06-1999	US 6030718 A	29-02-2000
		AU 1088999 A	15-06-1999